

SC0 HYDRO SEALANT

Description:

Innovacar's SC0 Hydro **Sealant** is a water-based **nanotechnology car spray sealant** suitable for body and paintwork. Due to its unique and innovative formulation, it is able to create a chemical and molecular barrier coating. With nanotechnology, it will be possible to protect the car body for several months.

In detail, it is an innovative solution that has the following features:

- **Protective chemical barrier:** through the siloxanes and fluoropolymers in the water-based formula, a nanotechnological chemical and molecular barrier is created, which protects and envelops the car bodywork, making it highly resistant.
- **Mirror effect and colour depth:** its unique formula creates a mirror effect and gives depth of colour.
- **Greater water repellent effect:** has an incredible water repellent and rainproof effect. It protects against limescale during the curing time, which is when the coatings harden.
- **Silk effect:** thanks to the protective barrier, the surface of the bodywork will be smooth to the touch.
- **Suitable for all surfaces:** thanks to the absence of petroleum distillates, it is suitable to withstand high temperatures and can be used directly on painted surfaces.
- **Long lasting:** the protective effect lasts up to 5 months if applied alone on the car after being cleaned properly with SP1 Prewash and S2 Foamy. The protection can last up to 9 months, if combined with W1 Quick Detailer used 20 minutes after the first application of SC0 Hydro Sealant and maintained over time with H2O Coat, every 3 washes.
- **Suitable for cars with and withing coating:** it is a product that can be used both on cars that have benefitted from a coating and/or polishing process, and on cars that have not been treated. This also makes it perfect for classic cars, the original paint condition of which must be preserved as much as possible.

Directions for use:

How to protect the car bodywork and apply the SC0 Hydro Sealant spray:

1. Clean the car in prewash with SP1 Prewash, in the wash step with S2 Foamy and use the specific Innovacar products as support for the various contaminations:
 - a. Use DS Scale for limescale.
 - b. Use D3 Tar for tar and resin.
 - c. Use D1 Iron for ferrous and metallic residue.
 - d. Use D2 Check for wax residue and polish or abrasive paste fillers.
2. Make sure the car surface is dry.
3. Apply 2-3 sprays of SC0 Hydro Sealant on the low pile microfibre cloth.
4. Apply panel by panel in a crisscross manner: then proceed by applying the product horizontally from right to left all over the area and then start again vertically, from top to bottom, along the same area
5. Go over the surface again with a medium/long fibred microfibre cloth with circular movements, turning it over often to remove any excess.
6. Wait up to 7 hours after the application for complete activation. The effect lasts up to 5 months.
7. 20 minutes after application you can use W1 Quick Detailer to finish the surface. Maintain it over time with H2O Coat every 3 washes to enhance the protective effect up to 9 months.

Use: use the product undiluted.

Precautions: Do not apply under the sun and on hot parts. The best performance is obtained with a completely decontaminated and clean surface.

FRA-BER s.r.l.

T +39 0363 905287

F +39 0363 905290

SEDE LEGALE

REGISTERED OFFICE

Via San Paolo n. 7
20121, Milano (MI) Italy

SEDE OPERATIVA

OPERATING OFFICE

Via M. Merisi 40-46
24051, Antegnate (BG) Italy



www.innovacar.it

info@innovadetailing.it

C.F. / P.IVA 03351820166

Caution:

Observe the advice on the safety data sheet when handling the product.

Technical features:

Appearance and colour: white liquid

Odour: characteristic

pH: $5,8 \pm 0,5$

Flash point: $>60\text{ }^{\circ}\text{C}$

Relative density: $0,98\text{ g/cm}^3 \pm 0,05$

Solubility in water: soluble

Solubility in oil: insoluble

Storage:

Unopened and stored at room temperature away from direct sunlight.

Packaging:

PACKAGING	BOX	ITEM CODE
BOTTLE 100 ml	6 pz	79294 (Public)
BOTTLE 500 ml	6 pz	79295 (Public)
JERRY-CAN 4,54 L	4 pz	700097 (Public)

Fra-Ber s.r.l.

The above data do not constitute specifications and are subject to normal production tolerances.

The data contained is the result of technological research of our laboratory and is provided for information purposes only.

We exclude any liability arising from an incorrect choice of product and the lack of the necessary precautions, which must always be verified by the user.

FRA-BER s.r.l.

T +39 0363 905287

F +39 0363 905290

SEDE LEGALE

REGISTERED OFFICE

Via San Paolo n. 7
20121, Milano (MI) Italy

SEDE OPERATIVA

OPERATING OFFICE

Via M. Merisi 40-46
24051, Antegnate (BG) Italy



www.innovacar.it

info@innovadetailing.it

C.F. / P.IVA 03351820166