



Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)
Issue date: 4/11/2024 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Name : Wheel Kleen
Other means of identification : 111, 111G01, 111G05

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Automotive Care Products
Restrictions on use : Any use not specified

1.3. Supplier

3D International LLC
20724 Centre Pointe Pkwy #1
Santa Clarita, CA, 91350
USA
T (888) 999-7627

1.4. Emergency telephone number

Emergency number : CHEMTREC 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Corrosive to metals Category 1	H290	May be corrosive to metals
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 1	H314	Causes severe skin burns and eye damage
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Specific target organ toxicity (repeated exposure) Category 1	H372	Causes damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment – Acute Hazard Category 3	H402	Harmful to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS labeling

Hazard pictograms (GHS) :



Signal word (GHS) : Danger
Hazard statements (GHS) : H290 - May be corrosive to metals
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H372 - Causes damage to organs through prolonged or repeated exposure
H402 - Harmful to aquatic life

Precautionary statements (GHS) : P234 - Keep only in original container.
P260 - Do not breathe mist, spray, vapors.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection.
P301+P312 - If swallowed: Call a POISON CENTER, a doctor if you feel unwell.
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P330 - Rinse mouth.
P363 - Wash contaminated clothing before reuse.
P390 - Absorb spillage to prevent material-damage.
P405 - Store locked up.
P406 - Store in corrosive resistant container with a resistant inner liner.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS classification
Alcohols, C9-11, ethoxylated	CAS-No.: 68439-46-3	2 – 4	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412
D-Glucopyranose, oligomeric, undecyl glycoside	CAS-No.: 157707-87-4	0.5 – 1.5	Skin Irrit. 2, H315 Eye Dam. 1, H318
sodium hydroxide	CAS-No.: 1310-73-2	0.5 – 1.5	Skin Corr. 1A, H314
Sodium metasilicate	CAS-No.: 6834-92-0	0.5 – 1.5	Skin Corr. 1B, H314 STOT SE 3, H335
tetrasodium ethylene diamine tetraacetate	CAS-No.: 64-02-8	0.5 – 1.5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H302 Eye Dam. 1, H318 STOT RE 1, H372

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Wash skin with plenty of water. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Obtain emergency medical attention. Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Harmful if swallowed.
Symptoms/effects	: Causes damage to organs through prolonged or repeated exposure.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Causes severe skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Absorb spillage to prevent material-damage. Notify authorities if product enters sewers or public waters.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Stop leak, if possible without risk. Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
-----------------	---

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Absorb spillage to prevent material-damage.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : May be corrosive to metals.

Precautions for safe handling : Ensure good ventilation of the work station. Do not breathe mist, spray, vapors. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures : Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep in a cool, well-ventilated place away from heat.

Storage conditions : Keep cool. Protect from sunlight. Keep container closed when not in use.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Metals.

Packaging materials : Store always product in container of same material as original container. Store in corrosive resistant container with a resistant inner liner.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Wheel Kleen	
No additional information available	
Alcohols, C9-11, ethoxylated (68439-46-3)	
No additional information available	
sodium hydroxide (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH OEL Ceiling	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Sodium hydroxide
OSHA PEL TWA	2 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (Ceiling)	2 mg/m ³
D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4)	
No additional information available	

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

tetrasodium ethylene diamine tetraacetate (64-02-8)

No additional information available

Sodium metasilicate (6834-92-0)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Industrial and professional. Perform risk assessment prior to use. Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves. Wear water impervious gloves. Butyl rubber gloves. Nitrile rubber gloves.

Eye protection:

Chemical goggles or safety glasses.

Skin and body protection:

Wear suitable protective clothing.

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Use an approved respirator equipped with oil/mist cartridges.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid
Color	: Brown
Odor	: Characteristic
Odor threshold	: No data available
pH	: 13 (12 – 13)
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.032
Solubility	: Soluble in water
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Explosive properties : No data available
Oxidizing properties : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. May be corrosive to metals.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Wheel Kleen	
ATE (oral)	500 mg/kg body weight
Alcohols, C9-11, ethoxylated (68439-46-3)	
LD50 Oral rat	> 5000 mg/kg
LD50 Dermal rabbit	> 2000 mg/kg
D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4)	
LD50 Oral rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 Dermal rabbit	> 2000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
tetrasodium ethylene diamine tetraacetate (64-02-8)	
LD50 Oral rat	1913 mg/kg male; 1780 mg/kg female
ATE (oral)	1913 mg/kg body weight
ATE (gases)	4500 ppmV/4h
ATE (vapors)	11 mg/l/4h
ATE (dust, mist)	1.5 mg/l/4h

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Sodium metasilicate (6834-92-0)	
LD50 Dermal rat	> 5000 mg/kg body weight Animal: rat, Guideline: EPA OPPTS 870.1200 (Acute Dermal Toxicity)
LC50 Inhalation rat	> 2.06 mg/l air Animal: rat, Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
Sodium metasilicate (6834-92-0)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4)	
NOAEL (oral,rat,90 days)	≥ 1000 mg/kg body weight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
tetrasodium ethylene diamine tetraacetate (64-02-8)	
LOAEL (oral,rat,90 days)	60 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Animal sex: female, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
NOAEL (oral,rat,90 days)	6 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Sodium metasilicate (6834-92-0)	
NOAEL (oral,rat,90 days)	227 – 237 mg/kg body weight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Skin and eye contact. Inhalation.
Potential Adverse human health effects and symptoms	: Harmful if swallowed.
Symptoms/effects	: Causes damage to organs through prolonged or repeated exposure.
Symptoms/effects after inhalation	: Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.
Symptoms/effects after skin contact	: Causes severe skin burns.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Ecology - water	: Harmful to aquatic life.

Alcohols, C9-11, ethoxylated (68439-46-3)	
LC50 fish 1	5.7 (≥ 0) mg/l 96 h Pimephales promelas

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Alcohols, C9-11, ethoxylated (68439-46-3)	
EC50 crustacea	2.5 mg/l 48 h
D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4)	
LC50 fish 1	2.95 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 - Fish [2]	5.9 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
tetrasodium ethylene diamine tetraacetate (64-02-8)	
LC50 fish 1	121 mg/l 96 h
EC50 crustacea	> 114 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	50 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	≥ 25.7 mg/l Test organisms (species): Duration: '35 d'
Sodium metasilicate (6834-92-0)	
EC50 crustacea	1700 mg/l Test organisms (species): Daphnia magna

12.2. Persistence and degradability

Wheel Kleen	
Persistence and degradability	Not established.
Alcohols, C9-11, ethoxylated (68439-46-3)	
Persistence and degradability	Readily biodegradable.
Biodegradation	72 %

12.3. Bioaccumulative potential

Wheel Kleen	
Bioaccumulative potential	Not established.
Alcohols, C9-11, ethoxylated (68439-46-3)	
BCF fish 1	0.237 mg/kg
Bioaccumulative potential	Not expected to bioaccumulate.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Do not re-use empty containers.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

DOT NA No : UN1760
UN-No. (TDG) : UN1760
UN-No. (IMDG) : 1760
UN-No. (IATA) : 1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s. (sodium hydroxide)
Proper Shipping Name (TDG) : CORROSIVE LIQUID, N.O.S. (sodium hydroxide)
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S. (sodium hydroxide)
Proper Shipping Name (IATA) : CORROSIVE LIQUID, N.O.S. (sodium hydroxide)

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8
Hazard labels (DOT) : 8



TDG

Transport hazard class(es) (TDG) : 8
Hazard labels : 8



IMDG

Transport hazard class(es) (IMDG) : 8
Hazard labels (IMDG) : 8



IATA

Transport hazard class(es) (IATA) : 8
Hazard labels (IATA) : 8



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

14.6. Special precautions for user

DOT

UN-No.(DOT)	: UN1760
DOT Special Provisions (49 CFR 172.102)	: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3) TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively. TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters"

TDG

UN-No. (TDG)	: UN1760
Special Provisions	: 16 - 1) The technical name of the most dangerous substance related to the primary class must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(i)(A) of Part 3, Documentation. The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4, Dangerous Goods Safety Marks. 2) subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical: a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act".
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 1 L
Emergency Response Guide (ERG) Number	: 154
IMDG	
Special provision (IMDG)	: 274

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: B
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provision (IATA)	: A3, A803
ERG code (IATA)	: 8L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for: D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4).

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

sodium hydroxide (1310-73-2)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

Alcohols, C9-11, ethoxylated (68439-46-3)

Listed on the Canadian DSL (Domestic Substances List)

sodium hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List)

D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4)

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

tetrasodium ethylene diamine tetraacetate (64-02-8)

Listed on the Canadian DSL (Domestic Substances List)

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

EU-Regulations

Alcohols, C9-11, ethoxylated (68439-46-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

tetrasodium ethylene diamine tetraacetate (64-02-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Alcohols, C9-11, ethoxylated (68439-46-3)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

D-Glucopyranose, oligomeric, undecyl glycoside (157707-87-4)

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

tetrasodium ethylene diamine tetraacetate (64-02-8)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on Taiwan National Chemical Inventory

Listed on the Japanese ENCS (Existing New Chemical Substances) inventory

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on KECI (Korean Existing Chemicals Inventory)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Data sources

: Information from published literature and internal company data. Supplier's safety documents. Manufacturer Information. OSHA 29CFR 1910.1200 Hazard Communication Standard. ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information

: None.

Full text of H-phrases

H290	May be corrosive to metals
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Full text of H-phrases	
H315	Causes skin irritation
H318	Causes serious eye damage
H332	Harmful if inhaled
H335	May cause respiratory irritation
H372	Causes damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

Wheel Kleen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada Hazardous Products Regulations (HPR) / Règlement sur les produits dangereux (RPD)

Abbreviations and acronyms	
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.