



Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)
Issue date: 4/17/2026 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Ceramic Coating Plus
Product code : 940

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Automotive Care Products.
Restrictions on use : None known

1.4. Supplier's details

3D International
20724 Centre Pointe Pkwy #1
Santa Clarita, CA 91350
T 888-999-7627

1.5. Emergency phone number

Emergency number : (Chemical Spills, Leaks, Fire, Exposure or Accident only)
CHEMTREC 1-800-424-9300 (in the US & Canada)
1-703-527-3887 (Outside the US)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2	H225	Highly flammable liquid and vapor.
Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 1	H318	Causes serious eye damage.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H361 - Suspected of damaging fertility or the unborn child

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Precautionary statements (GHS US)	: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical, lighting, ventilating equipment. P242 - Use non-sparking tools. P243 - Take action to prevent static discharges. P261 - Avoid breathing vapors. P264 - Wash hands thoroughly after handling. P272 - Contaminated work clothing must not be allowed out of the workplace. P280 - Wear protective gloves, eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician. P302+P352 - If on skin: Wash with plenty of soap and water. P333+P313 - If skin irritation or rash occurs: Get medical attention. P362+P364 - Take off contaminated clothing and wash it before reuse. P308+P313 - If exposed or concerned: Get medical advice/attention. P370+P378 - In case of fire: Use ABC-powder, alcohol resistant foam, carbon dioxide (CO2) to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents and/or container to an approved waste disposal plant.
-----------------------------------	---

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

Mixtures

Name	Product identifier	Conc. (% w/w)
Hexamethyldisiloxane	CAS-No.: 107-46-0	25 – 50
Octamethylcyclotetrasiloxane	CAS-No.: 556-67-2	25 – 50
Ambient Cure Refractory Resin	CAS-No.: 3D-0001**	5 – 10
Decamethylcyclopentasiloxane	CAS-No.: 541-02-6	5-10
Bis(trimethoxysilylpropyl)amine	CAS-No.: 82985-35-1	1 – 5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Comments : ** Unique identifier is a company internal designation.

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: Move the affected person to fresh air. Get medical attention if symptoms occur.
First-aid measures after skin contact	: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: Causes skin irritation. May cause an allergic skin reaction.
Eyes	: May cause severe eye irritation and burns with pain, tearing, and redness. May cause permanent eye damage, vision impairment, and blurred vision.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Immediate medical attention is required for eye contact. Treat symptomatically.
-----------------------------------	---

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray or alcohol-resistant foam.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapour. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.
Explosion hazard	: Prolonged exposure to fire may cause containers to rupture/explode.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO ₂). Nitrogen oxides.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Fight fire from safe distance and protected location. Use water spray or fog for cooling exposed containers. Do not enter fire area without proper protective equipment, including respiratory protection. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Use self-contained breathing apparatus and chemically protective clothing. Do not attempt to take action without suitable protective equipment.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate ignition sources. Avoid contact with eyes, skin and clothing. Wear suitable protective clothing. Do not touch or walk on the spilled product.
------------------	---

For non-emergency personnel

Emergency procedures	: Keep unnecessary and unprotected personnel away from the spillage.
----------------------	--

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Environmental precautions : Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Use non-sparking tools. Absorb and/or contain spill with inert material, then place in suitable container.

Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing mist, vapors. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Store in dry, cool, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Protect from moisture. Store away from. Strong oxidizers. Keep container tightly closed.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Octamethylcyclotetrasiloxane (556-67-2)	
USA - AIHA - Occupational Exposure Limits	
WEEL TWA	10 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation to minimize mist and/or vapor concentrations.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration. Contact your glove supplier for selection assistance.
Eye protection:
Wear safety goggles or other eye protection to prevent eye contact.
Skin and body protection:
Wear suitable protective clothing

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Respiratory protection:

Not required for normal conditions of use. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear. Liquid.
Color	: clear
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≤ -6 °C
Flammability (solid, gas)	: Flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 0.88
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: Particle characteristics : Not applicable

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

Oxidizing Substances. alcohols.

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Decamethylcyclopentasiloxane (541-02-6)

LD50 oral rat	> 5000 mg/kg body weight (OECD 401 method)
LD50 dermal rabbit	> 2000 mg/kg body weight (OECD 402 method)
LC50 Inhalation - Rat (Dust/Mist)	8.67 mg/l/4h

Ambient Cure Refractory Resin (3D-0001**)

LD50 oral rat	500 mg/kg
---------------	-----------

Hexamethyldisiloxane (107-46-0)

LD50 oral rat	> 5000 mg/kg Source: IUCLID
LD50 oral	12160 mg/kg
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LD50 dermal	12160 mg/kg
LC50 Inhalation - Rat [ppm]	15956 ppm Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapors)	106 mg/l/4h

Bis(trimethoxysilylpropyl)amine (82985-35-1)

LD50 oral rat	3750 mg/kg
LD50 dermal rabbit	11865 mg/kg

Octamethylcyclotetrasiloxane (556-67-2)

LD50 oral rat	> 4800 mg/kg
LD50 dermal rat	> 2375 mg/kg
LC50 Inhalation - Rat (Vapors)	36 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Decamethylcyclopentasiloxane (541-02-6)

NOAEL (oral,rat,90 days)	≥ 1000 mg/kg body weight (OECD 408 method)
NOAEL (dermal,rat/rabbit,90 days)	≥ 1600 mg/kg body weight (rat) (OECD 410 method)

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Hexamethyldisiloxane (107-46-0)	
NOAEL (oral,rat,28 days)	160 mg/kg bw/day
NOAEL (dermal,rat/rabbit,28 days)	1000 mg/kg bw/day
NOAEL (oral,rat,90 days)	160 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal,rat/rabbit,90 days)	≥ 1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Aspiration hazard	: Not classified
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: Causes skin irritation. May cause an allergic skin reaction.
Eyes	: May cause severe eye irritation and burns with pain, tearing, and redness. May cause permanent eye damage, vision impairment, and blurred vision.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Decamethylcyclopentasiloxane (541-02-6)	
LC50 - Fish [1]	> 16 µg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	> 2.9 µg/l daphnia
EC50 96h - Algae [1]	> 0.012 mg/l
NOEC chronic fish	0.014 mg/l Oncorhynchus mykiss (Rainbow trout)
NOEC chronic crustacea	0.015 mg/l Daphnia magna (Water flea)

Hexamethyldisiloxane (107-46-0)	
LC50 - Fish [1]	0.46 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 0.93 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.2 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 0.55 mg/l
NOEC chronic crustacea	0.08 mg/l
NOEC chronic algae	0.09 mg/l

Bis(trimethoxysilylpropyl)amine (82985-35-1)	
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 72h - Algae [1]	31 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	36 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Bis(trimethoxysilylpropyl)amine (82985-35-1)	
NOEC chronic algae	6.26 mg/l
Octamethylcyclotetrasiloxane (556-67-2)	
LC50 - Fish [1]	> 22 µg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	> 15 µg/l Daphnia magna (Water flea)
NOEC chronic fish	0.0044 mg/l Oncorhynchus mykiss (Rainbow trout)
NOEC chronic crustacea	0.015 mg/l Daphnia magna (Water flea)

12.2. Persistence and degradability

Ceramic Coating Plus	
Persistence and degradability	No additional information available.
Decamethylcyclopentasiloxane (541-02-6)	
Persistence and degradability	Not rapidly degradable
Ambient Cure Refractory Resin (3D-0001**)	
Persistence and degradability	No additional information available.
Hexamethyldisiloxane (107-46-0)	
Persistence and degradability	Not readily biodegradable.
Bis(trimethoxysilylpropyl)amine (82985-35-1)	
Persistence and degradability	Not readily biodegradable.
Octamethylcyclotetrasiloxane (556-67-2)	
Persistence and degradability	Not rapidly degradable
Biodegradation	3.7 % (29 days)

12.3. Bioaccumulative potential

Decamethylcyclopentasiloxane (541-02-6)	
Partition coefficient n-octanol/water (Log Pow)	5.2
Hexamethyldisiloxane (107-46-0)	
BCF - Fish [1]	1290 – 2410 l/kg
Partition coefficient n-octanol/water (Log Pow)	4.2
Bis(trimethoxysilylpropyl)amine (82985-35-1)	
Partition coefficient n-octanol/water (Log Pow)	-3.73 Source: Episuite
Octamethylcyclotetrasiloxane (556-67-2)	
Partition coefficient n-octanol/water (Log Pow)	5.1

12.4. Mobility in soil

Decamethylcyclopentasiloxane (541-02-6)	
Mobility in soil	16000 Source: HSDB

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Hexamethyldisiloxane (107-46-0)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.34
--	------

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No

SECTION 13 Disposal considerations

Regional waste regulation	: Dispose of in accordance with applicable federal, state, and local regulations.
Waste treatment methods	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
UN1993	UN1993	1993	1993
14.2. Proper Shipping Name			
Flammable liquids, n.o.s. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin)	Flammable liquids, n.o.s. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin)	FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin)	Flammable liquid, n.o.s. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin)
Transport document description			
UN1993 Flammable liquids, n.o.s. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin), 3, II	Flammable liquids, n.o.s. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin), 3, II	UN 1993 FLAMMABLE LIQUID, N.O.S. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin), 3, II (-6°C c.c.)	UN 1993 Flammable liquid, n.o.s. (Hexamethyldisiloxane ; Ambient Cure Refractory Resin), 3, II
14.3. Transport hazard class(es)			
3	3	3	3
			
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment: No	Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes
Note: Inner packages with less than 5 liters of liquid are exempt from being shipped as a marine pollutant per IMDG Code 2.10.2.7 and ICAO Special Provision A197.			

14.6. Transport in bulk

Not applicable

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

14.7. Special precautions for user

DOT
UN-No. (DOT) : UN1993

TDG
No data available

IMDG
No data available

IATA
No data available

SECTION 15 Regulatory information

15.1. Federal regulations

Ceramic Coating Plus

SARA Section 311/312 Hazard Classes	Refer to Section 2 for OSHA Hazard Classification.
-------------------------------------	--

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventor.

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Octamethylcyclotetrasiloxane	CAS-No. 556-67-2	25 – 50%
------------------------------	------------------	----------

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Decamethylcyclopentasiloxane (541-02-6)

Listed on the Canadian DSL (Domestic Substances List)

Hexamethyldisiloxane (107-46-0)

Listed on the Canadian DSL (Domestic Substances List)

Bis(trimethoxysilylpropyl)amine (82985-35-1)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Octamethylcyclotetrasiloxane (556-67-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

Ceramic Coating Plus

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

National regulations

Ceramic Coating Plus
Contains substance(s) listed on NDSL
Decamethylcyclopentasiloxane (541-02-6)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Hexamethyldisiloxane (107-46-0)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Octamethylcyclotetrasiloxane (556-67-2)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Issue date : 4/17/2026

Data sources : This safety data sheet was compiled with data and information from the following sources :
ECHA, ECOSAR, HSDB, SIDS SIAP, CESAR, Chemical DB.

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H361	Suspected of damaging fertility or the unborn child

Indication of changes:
New SDS.

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.