



Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)
Issue date: 5/27/2026 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Trade name : Therapy Final Polish
Product code : B1908, B190Q

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Automotive Care Products.
Restrictions on use : None known

1.4. Supplier's details

P&S Sales, Inc.
20943 Cabot Blvd.
Hayward, CA 94545
T 510-732-2628
dave@pssales.com

1.5. Emergency phone number

Emergency number : 1-800-255-3924

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 4	H227	Combustible liquid.
Reproductive toxicity, Category 2	H361	Suspected of damaging fertility or the unborn child.
Aspiration hazard, Category 1	H304	May be fatal if swallowed and enters airways.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H227 - Combustible liquid
H304 - May be fatal if swallowed and enters airways
H361 - Suspected of damaging fertility or the unborn child
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear protective gloves.
P301+P310 - If swallowed: Immediately call a POISON CENTER, a doctor.

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

P331 - Do NOT induce vomiting.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P370+P378 - In case of fire: Use Water fog, ABC-powder, carbon dioxide (CO₂), foam to extinguish.
P403 - Store in a well-ventilated place.
P405 - Store locked up.
P501 - Dispose of to an approved waste disposal plant to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

None known

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : None known.

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

Mixtures

Name	Product identifier	Conc. (% w/w)
Aluminum Oxide	CAS-No.: 1344-28-1	10 – 30
Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	10-30
Propylene glycol	CAS-No.: 57-55-6	1 – 5
Octamethylcyclotetrasiloxane	CAS-No.: 556-67-2	0.1-1

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret
Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation : Move the affected person to fresh air. Get medical attention if symptoms occur.
First-aid measures after skin contact : Gently wash with plenty of soap and water. Get medical attention if irritation occurs and persists.
First-aid measures after eye contact : Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion : Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms/effects, acute and delayed

Inhalation : May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin : May cause slight irritation to the skin.
Eyes : May cause minor eye irritation.
Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard.
Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Chronic symptoms : Suspected of damaging fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Aspiration hazard. If accidentally swallowed obtain immediate medical attention.

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- | | |
|--------------------------------|--|
| Suitable extinguishing media | : Dry chemical, CO2, or water spray or regular foam. |
| Unsuitable extinguishing media | : Do not use a solid water stream as it may scatter and spread fire. |

5.2. Specific hazards arising from the chemical

- | | |
|--|---|
| Fire hazard | : This product is not classified as flammable or combustible. Could burn but does not ignite readily. |
| Hazardous decomposition products in case of fire | : Toxic fumes may be released. Carbon oxides (CO, CO2). |

5.3. Special protective equipment and precautions for fire-fighters

- | | |
|--------------------------------|--|
| Firefighting instructions | : Cool down the containers exposed to heat with a water spray. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. |

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|---|
| General measures | : Wear suitable protective clothing. Avoid contact with eyes, skin and clothing. Remove ignition sources. |
|------------------|---|

For non-emergency personnel

- | | |
|----------------------|--|
| Emergency procedures | : Keep unnecessary and unprotected personnel away from the spillage. |
|----------------------|--|

For emergency responders

- | | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

- | | |
|---------------------------|-------------------------------------|
| Environmental precautions | : Avoid release to the environment. |
|---------------------------|-------------------------------------|

6.2. Methods and materials for containment and cleaning up

- | | |
|-------------------------|---|
| For containment | : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. |
| Methods for cleaning up | : Take up liquid spill into absorbent material. |
| Other information | : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13). |

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- | | |
|-------------------------------|--|
| Precautions for safe handling | : Avoid contact with eyes, skin and clothing. Wash hands with water and soap. Ensure adequate ventilation. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including incompatibilities

- | | |
|------------------------|---|
| Storage conditions | : Store locked up. No special storage required. |
| Incompatible materials | : None known. |

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Propylene glycol (57-55-6)	
USA - AIHA - Occupational Exposure Limits	
WEEL TWA	10 mg/m³
Aluminum Oxide (1344-28-1)	
USA - OSHA - Occupational Exposure Limits	
Local name	alpha-Alumina
OSHA PEL (TWA)	15 mg/m³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Octamethylcyclotetrasiloxane (556-67-2)	
USA - AIHA - Occupational Exposure Limits	
WEEL TWA	10 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls	: No particular/specific measures required.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear impervious gloves. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Use suitable eye protection
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: White. Liquid.
Color	: White.
Odor	: Fruity
Odor threshold	: No data available
pH	: 7
Melting point	: 32 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 80 °C (176°F)
Flammability (solid, gas)	: Combustible liquid.

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.026
Solubility	: Dispersible. in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosion limits	: No data available
Explosive properties	: None.
Oxidizing properties	: None.
Particle characteristics	: No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distallates (petroleum), hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -
Propylene glycol (57-55-6)	
LD50 oral rat	22000 mg/kg body weight Animal: rat

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Propylene glycol (57-55-6)	
LD50 dermal rat	20800 mg/kg
LD50 dermal rabbit	> 2000 mg/kg body weight Animal: rabbit
LC50 Inhalation - Rat	> 44.9 mg/l air Animal: rat, Guideline: other:
Aluminum Oxide (1344-28-1)	
LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 7.6 mg/l 1 h
Octamethylcyclotetrasiloxane (556-67-2)	
LD50 oral rat	> 4800 mg/kg
LD50 dermal rat	> 2375 mg/kg
LC50 Inhalation - Rat (Vapors)	36 mg/l/4h
Skin corrosion/irritation	: Not classified pH: 7
Serious eye damage/irritation	: Not classified pH: 7
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg body weight Animal: rat, Animal sex: male
Aluminum Oxide (1344-28-1)	
NOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Distillates (petroleum), hydrotreated light (64742-47-8)	
NOAEL (oral,rat,90 days)	750 mg/kg body weight Animal: rat, Animal sex: female
NOAEC (inhalation,rat,vapor,90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Propylene glycol (57-55-6)	
NOAEL (subchronic,oral,animal/male,90 days)	443 mg/kg body weight Animal: cat, Animal sex: male
Aluminum Oxide (1344-28-1)	
NOAEC (inhalation,rat,dust/mist/fume,90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: May cause slight irritation to the skin.
Eyes	: May cause minor eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.
Chronic symptoms	: Suspected of damaging fertility or the unborn child.

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Hazardous to the aquatic environment, short-term (acute) : Not classified.
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Distillates (petroleum), hydrotreated light (64742-47-8)	
EC50 - Crustacea [1]	> 1000 mg/l

Propylene glycol (57-55-6)	
LC50 - Fish [1]	51400 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	43500 mg/l
LC50 - Fish [2]	51600 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 72h - Algae [1]	19300 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	24200 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	19100 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	19000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Aluminum Oxide (1344-28-1)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Octamethylcyclotetrasiloxane (556-67-2)	
LC50 - Fish [1]	> 22 µg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	> 15 µg/l Daphnia magna (Water flea)
NOEC chronic fish	0.0044 mg/l Oncorhynchus mykiss (Rainbow trout)
NOEC chronic crustacea	0.015 mg/l Daphnia magna (Water flea)

12.2. Persistence and degradability

Therapy Final Polish	
Persistence and degradability	No additional information available.

Distillates (petroleum), hydrotreated light (64742-47-8)	
Persistence and degradability	Not rapidly degradable

Propylene glycol (57-55-6)	
Persistence and degradability	Readily biodegradable.

Aluminum Oxide (1344-28-1)	
Persistence and degradability	Biodegradation is not applicable to inorganic compounds.

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Octamethylcyclotetrasiloxane (556-67-2)	
Persistence and degradability	Not rapidly degradable
Biodegradation	3.7 % (29 days)

12.3. Bioaccumulative potential

Propylene glycol (57-55-6)	
Partition coefficient n-octanol/water (Log Pow)	-0.92
Bioaccumulative potential	Low bioaccumulation potential.

Octamethylcyclotetrasiloxane (556-67-2)	
Partition coefficient n-octanol/water (Log Pow)	5.1

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified
Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation : Dispose of in accordance with applicable federal, state, and local regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
Not regulated for transport			
14.2. Proper Shipping Name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

14.6. Transport in bulk

Not applicable

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

IATA
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.		
Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S		
Octamethylcyclotetrasiloxane	CAS-No. 556-67-2	0.1-1%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
Aluminum Oxide	CAS-No. 1344-28-1	10 – 30%

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated light (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

Propylene glycol (57-55-6)

Listed on the Canadian DSL (Domestic Substances List)

Aluminum Oxide (1344-28-1)

Listed on the Canadian DSL (Domestic Substances List)

Octamethylcyclotetrasiloxane (556-67-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Propylene glycol (57-55-6)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Therapy Final Polish

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)

Octamethylcyclotetrasiloxane (556-67-2)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

 **WARNING:** This product can expose you to Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Propylene glycol(57-55-6)	U.S. - New Jersey - Right to Know Hazardous Substance List
Aluminum Oxide(1344-28-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16 Other information

According to 29CFR 1910.1200 OSHA Hazard Communication Standard (HCS 2024) and the Hazardous Products Regulation (WHMIS 2015 rev 2022)
Issue date : 5/27/2026

Full text of hazard classes and H-statements	
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H361	Suspected of damaging fertility or the unborn child

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.